



## tesa® 7133

Filmic masking tape

tesa® 7133 is a Polypropylene film tape with a natural rubber adhesive.

Features & benefits:

- Easy to remove
- Paint anchorage
- Power wash resistance
- Scratch resistance
- Flame retardant

### Primary intended use:

- Masking during multi color painting
- Protection against dirt and damage of painted and unpainted plastic parts
- Temporary surface protection for any device with cosmetic surfaces.

### Technical Data

Backing:	Polypropylene film
Type of Adhesive:	Natural Rubber
Color:	Blue
Total Thickness:	.0031" (80 µm)
Adhesion to Steel:	16.4 oz/in (1.8 N/cm)
Tensile Strength:	75.9 psi (133 N/cm)
Elongation:	30%
Temperature resistance:	248 °F / 120 °C



For more information, product sample, laser or plotter cut sample parts,  
Contact Marian Inc.

Phone: 800.773.0062

email: [Sales@marianinc.com](mailto:Sales@marianinc.com)

Visit our website:

<http://www.marianinc.com/>

page 1 of 1

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.